

IN THE CLAIMS:

Cancel Claims 1-3 and 15-19.

1.-3. (canceled)

4. (Previously Presented) An apparatus for generating and detecting ultrasonic surface displacements on a remote target comprising:

a first pulsed laser to generate a first pulsed laser beam to illuminate a portion of a surface of the remote target and produce ultrasonic surface displacements substantially within the illuminated portion of the surface of the remote target;

a second pulsed laser to generate a second pulsed laser beam coaxial with said first pulsed laser beam, wherein the second pulsed laser beam substantially illuminates the portion of the surface illuminated by the first pulsed laser beam to detect the ultrasonic surface displacements on the surface of the remote target;

a scanning optical assembly operable to direct the first pulsed laser beam and second pulsed laser beam to the surface of the remote target;

collection optics, optically coupled to the scanning optical assembly, operable to collect phase modulated light from the second pulsed laser beam either reflected or scattered by the remote target;

an interferometer self-stabilized with the phase modulated light, wherein the interferometer is operable to process the phase modulated light and generate at least one output signal; and

a processor operable to:

process the at least one output signal to obtain data representative of the ultrasonic surface displacements on the surface of the remote target; and

process the data representative of the surface displacements to assess the structural integrity of the remote target.

5. (Original) The apparatus of Claim 4 further comprising an intensity controller to adjust on a pulse-by-pulse basis the intensity of the second pulsed laser beam in proportion to the intensity of the phase modulated light collected by the collection optics.

6. (Original) The apparatus of Claim 4 wherein the first pulsed laser emits a laser beam of coherent light of about 10 microns in wave length.

7. (Original) The apparatus of Claim 4 wherein the interferometer is self-stabilized using substantially 100% of the phase modulated light delivered to the interferometer by the collection optics.

8. (Original) The apparatus of Claim 4 further comprising an optical ranging unit to calculate a distance by which the remote target is separated from the apparatus.

9. (Previously Presented) A large area composite inspection apparatus for measuring ultrasonic surface displacements on a surface of a remote target comprising:

a detection laser to generate a pulsed laser beam to detect the ultrasonic surface displacements on the surface of the remote target;

a scanning optical assembly operable to scan the pulsed laser beam across the surface of the remote target;

collection optics, optically coupled to the scanning optical assembly for collecting phase modulated light from the pulsed laser beam either reflected or scattered by the remote target;

an interferometer to process the phase modulated light collected by the collection optics, wherein the interferometer is self-stabilized with the collected phase modulated light either reflected or scattered by the remote target;

said interferometer comprising:

a first cavity having a first confocal lens structure; a second cavity having a second confocal lens structure; a device for dividing incoming de-polarized light into a first polarized light component and a second polarized light component wherein said device also directs said first and second polarized light components into the first and second cavities;

a control system to adjust said first and second cavities such that a ratio of light transmitted through each cavity to light reflected back through each cavity remains substantially constant; and

a processor to process the light transmitted through the first cavity, the light reflected back through the first cavity, the light transmitted through the second cavity, and the light reflected back through the second cavity, all in order to obtain data representative of the ultrasonic surface displacements on the surface of the remote target.

10. (Original) The large area composite inspection apparatus of claim 9 further comprising an intensity controller which adjusts on a pulse-by-pulse basis the intensity of the pulsed laser beam in proportion to the intensity of the phase modulated light collected by the collection optics.

11. (Original) The large area composite inspection apparatus of claim 9 further comprising a positioning apparatus to move the detection laser across the surface of the remote target and then record and index the data detected by the large area composite inspection apparatus.

12. (Original) The large area composite inspection apparatus of claim 9 wherein the positioning apparatus is a gantry positioning apparatus.

13. (Original) The large area composite inspection apparatus of claim 9 further comprising a generation laser to generate a pulsed laser beam to detect generate the ultrasonic surface displacements on the surface of the remote target.

14. (Original) The large area composite inspection apparatus of claim 9 wherein the generation laser and the detection laser coaxially apply laser beams to the surface of the remote target.

15.-19. (canceled)